

Crown Bevcan, Europe & Middle East

www.crowncork.com

Status: **Approved**

Issue Date: **Wednesday, March 28, 2018**

Version Number: **2**

Authorised By: **Florent Gourven**

Component Weight :	<b>2.49g</b>
Compound Weight :	<b>21mg +/- 6</b>
Nominal Material Thickness :	<b>0.208mm</b>
Component Lacquered Material Thickness :	<b>0.218mm nom.</b>
Minimum Peaking Pressure :	<b>90psi</b>
Minimum Vent Pressure :	<b>90psi</b>
Internal Lacquer Specification :	<b>PVC Free</b>
External Lacquer Specification :	<b>Epoxy</b>
Lining Compound Specification :	<b>Water Based</b>
Compound Placement :	<b>High on Shoulder (HOS)</b>
Stacking Rate :	<b>26 +/- 2 per 2"</b>



**202 ISE - LOE**  
Large Aperture

## End Specification

Entity Code	Entity Description	Value	Tolerance
ED	Curly External Diameter	2.336 inch	±.010
EL	Curly Tip Diameter	2.270 inch	min.
EB	Curly Height	.078 inch	±.006
HK	Converted Countersink Depth	.243 inch	±.005
EJ	Compound Shoulder Clearance	.220 inch	±.020
EK	Compound Edge Clearance	.039 inch	±.020

